



DVI Distributor, OVD14/ OVD18

Description

OPTICIS DVI Distributor, OVD 14 or OVD18 makes one(1) DVI video source split into four(4) or eight(8) DVI displays, respectively without any signal loss or digital noise. Also, HDMI source and displays are compatible by using HDMI-DVI cable.

Technical Features

Model Name	OVD14	OVD18
Input Signal	DVI (TMDS), Single Link	
Output Signal	DVI Single Link , 4port,	DVI Single Link , 8port,
Resolution	VGA to WUXGA, 480p to 1080p	
Receptacle	DC Power Jack DVI	
Power Supply	DC +5V , 2.6A	
Dimension(mm)	160 x 91 x 25	240 x 103 x 25
Weight(kg)	0.24	0.38
Operating Temp.	0°C~40°C	0°C~48°C
Storage Temp.	-20°C~45°C	
Operating Humidity	30%~80%	
Storage Humidity	60%	
Power Consumption	6W	10W

Specification

- Offers an EDID program feature
- Supports DDC/HDCP
- Supports up to WUXGA (1920x1200), at 60Hz and HD 1080p (1920x1080).
- Provides Power, Sync LED indicators.
- Compatible with HDMI-DVI cable.

Optolinks

HQ Address
46 Corporate Park #130
Irvine, CA 92606
949-701-4742
info@VigilLink.com

All contents are subject to be changed without prior notice.